








SEC-EXACT

Cordless center-grip screwdrivers

Cordless center-grip screwdrivers

SEC-EXACT

- ▶ Highest repeatability:
Improved accuracy! $Cmk \geq 2,0$
Also the reaction forces could be improved.
- ▶ Lowest weight in class:
The new SEC-EXACT models use the 9.6 volt batteries only, reducing weight by 300 grams!
- ▶ Huge speed range of the complete series
- ▶ Broad torque range
- ▶ Illumination of the work area.
- ▶ Overload protection for the PCB, the motor and the battery pack.
- ▶ Best ergonomics:
Small size and very well balanced.
One handed operation for On/Off and Left/Right.
- ▶ Robust and durable tool with the well known components of the EXACT range.
- ▶ Proven and highly efficient battery technology in production quality.
You can still use your existent charging technology, battery packs and protective covers.

SEC-EXACT	Order number	Torque on hard joint per ISO 5393 (Nm)	Torque on soft joint per ISO 5393 (Nm)
SEC-EXACT 1106 highest speed for short cycle times 	0 602 492 431	1 – 6 (0.7 – 4.4 ft.-lbs.)	1 – 6 (0.7 – 4.4 ft.-lbs.)
	0 602 492 432	1 – 6 (0.7 – 4.4 ft.-lbs.)	1 – 6 (0.7 – 4.4 ft.-lbs.)
SEC-EXACT 908 combination of speed and torque 	0 602 492 443	2 – 8 (1.5 – 5.9 ft.-lbs.)	2 – 8 (1.5 – 5.9 ft.-lbs.)
	0 602 492 444	2 – 8 (1.5 – 5.9 ft.-lbs.)	2 – 8 (1.5 – 5.9 ft.-lbs.)
SEC-EXACT 610 power and speed 	0 602 492 445	2 – 10 (1.5 – 7.4 ft.-lbs.)	2 – 10 (1.5 – 7.4 ft.-lbs.)
	0 602 492 446	2 – 10 (1.5 – 7.4 ft.-lbs.)	2 – 10 (1.5 – 7.4 ft.-lbs.)
SEC-EXACT 459 the model fits every application 	0 602 492 435	2 – 9 (1.5 – 6.7 ft.-lbs.)	2 – 9 (1.5 – 6.7 ft.-lbs.)
	0 602 492 436	2 – 9 (1.5 – 6.7 ft.-lbs.)	2 – 9 (1.5 – 6.7 ft.-lbs.)
SEC-EXACT 412 high torque with low weight 	0 602 492 441	2 – 12 (1.5 – 9 ft.-lbs.)	2 – 12 (1.5 – 9 ft.-lbs.)
	0 602 492 442	2 – 12 (1.5 – 9 ft.-lbs.)	2 – 12 (1.5 – 9 ft.-lbs.)
SEC-EXACT 402 very precise in the lower torque range 	0 602 492 433	0.5 – 2 (0.4 – 1.5 ft.-lbs.)	0.5 – 2 (0.4 – 1.5 ft.-lbs.)
	0 602 492 434	0.5 – 2 (0.4 – 1.5 ft.-lbs.)	0.5 – 2 (0.4 – 1.5 ft.-lbs.)
SEC-EXACT 212 slow screwdriver e.g. for hose clamps 	0 602 492 439	2 – 12 (1.5 – 9 ft.-lbs.)	2 – 12 (1.5 – 9 ft.-lbs.)
	0 602 492 440	2 – 12 (1.5 – 9 ft.-lbs.)	2 – 12 (1.5 – 9 ft.-lbs.)

C-EXACT

EXACT

BT-EXACT

SEC-EXACT

ACCESSORIES

No-load speed (min ⁻¹)	Bit holder	Battery specifications	Direction of rotation	Weight (kg / lbs)	Features	Included accessories
1100	¼"	–	R/L	0.8 / 1.76	0.7 repeat protection	Torque adjustment tool black color ring
1100	¼"	9.6 V / 1.7 Ah	R/L	1.2 / 2.6	0.7 repeat protection	
900	¼"	–	R/L	0.8 / 1.76	0.7 repeat protection	Torque adjustment tool orange color ring
900	¼"	9.6 V / 1.7 Ah	R/L	1.2 / 2.6	0.7 repeat protection	
600	¼"	–	R/L	0.8 / 1.76	0.7 repeat protection	Torque adjustment tool grey color ring
600	¼"	9.6 V / 1.7 Ah	R/L	1.2 / 2.6	0.7 repeat protection	
450	¼"	–	R/L	0.8 / 1.76	0.7 repeat protection	Torque adjustment tool light blue ring
450	¼"	9.6 V / 1.7 Ah	R/L	1.2 / 2.6	0.7 repeat protection	
400	¼"	–	R/L	0.8 / 1.76	0.7 repeat protection	Torque adjustment tool red color ring
400	¼"	9.6 V / 1.7 Ah	R/L	1.2 / 2.6	0.7 repeat protection	
400	¼"	–	R/L	0.8 / 1.76	0.7 repeat protection	Torque adjustment tool light green color ring
400	¼"	9.6 V / 1.7 Ah	R/L	1.2 / 2.6	0.7 repeat protection	
275	¼"	–	R/L	0.8 / 1.76	0.7 repeat protection	Torque adjustment tool white color ring
275	¼"	9.6 V / 1.7 Ah	R/L	1.2 / 2.6	0.7 repeat protection	