

# Angle shut-off wrenches with shut-off clutch



For screws  
from M 5 to M 16

**Angle shut-off wrenches  
180 watts**



**CLEAN**

**Angle shut-off wrenches  
370 watts**



**Angle shut-off wrenches  
370 watts**



- ▶ Shut-off clutch for very fine torque setting and minimal torque dispersion
- ▶ Long lifetime
- ▶ External torque setting
- ▶ Small, rotating angle head
- ▶ Exhaust air hose optional
- ▶ Low-noise

Part number	Screw dia. Quality category 8.8	Tightening torque (Nm) hard screwdriving application 30°
0 607 453 621	M 5	1.5–8
0 607 453 622	M 5	1.5–8
0 607 453 623*	M 6	2–10
0 607 453 624*	M 6	2–10
0 607 453 625*	M 8	2–15
0 607 453 626*	M 8	2–15
<hr/>		
0 607 451 600	M 10	7–27
0 607 451 601	M 10	7–27
0 607 451 604	M 10	7–30
<hr/>		
0 607 451 606	M 10	7–27
0 607 451 607	M 10	7–27
0 607 451 605	M 10	7–30
0 607 451 602	M 10	7–28
0 607 451 603	M 10	7–28

Tightening torque (Nm) soft screwdriving application 720°	No-load speed (rpm)	Direction of rotation	Air consumption under load (l/s) (cfm)	Weight (kg)	Hex tool holder = internal hexagon Square = external square	Connecting thread	Hose inner diameter (mm)	Comments	Comes complete with
1.5-7	670	R/L	4.7	1.1	1/4" square	G 1/4"	6	Centralised exhaust air guidance	Chuck key Hose nipple Clutch spring (yellow) or *clutch spring (blue)
			10.0						
1.5-7	670	R/L	4.7	1.1	1/4" hex	G 1/4"	6		
			10.0						
2-9	420	R/L	4.7	1.1	1/4" square	G 1/4"	6		
			10.0						
2-9	420	R/L	4.7	1.1	1/4" hex	G 1/4"	6		
			10.0						
2-14	260	R/L	4.7	1.1	1/4" square	G 1/4"	6		
			10.0						
2-14	260	R/L	4.7	1.1	3/8" square	G 1/4"	6		
			10.0						
7-24	360	R/L	11.9	1.6	3/8" square	G 1/4"	10	Decentralised exhaust air guidance	Locking hook Hose nipple G 1/4" Silencer - Plastic - Sintered metal
			25.2						
7-24	360	R/L	11.9	1.6	1/4" hex	G 1/4"	10		
			25.2						
7-30	280	R/L	11.9	1.6	3/8" square	G 1/4"	10		
			25.2						
7-24	360	R/L	11.9	1.5	3/8" square	G 1/4"	10	Centralised exhaust air guidance	Locking hook Hose nipple G 1/4"
			25.2						
7-24	360	R/L	11.9	1.5	1/4" hex	G 1/4"	10		
			25.2						
7-30	280	R/L	11.9	1.5	3/8" square	G 1/4"	10		
			25.2						
7-26	360	R	11.1	1.5	3/8" square	G 1/4"	10		
			23.5						
7-26	360	R	11.1	1.5	1/4" hex	G 1/4"	10		
			23.5						

# Angle shut-off wrenches with shut-off clutch

- ▶ Shut-off clutch for very fine torque setting and minimal torque dispersion
- ▶ Long lifetime
- ▶ External torque setting
- ▶ Small, rotating angle head
- ▶ Exhaust air hose optional
- ▶ Low-noise

For screws  
from M 5 to M 16

**Angle shut-off wrenches  
400 watts**



**Angle shut-off wrenches  
550 watts**



**Angle shut-off wrenches  
740 watts**



Part number	Screw dia. Quality category 8.8	Tightening torque (Nm) hard screwdriving application 30°
0 607 461 604	M 10	8–30
0 607 461 605	M 10	8–30
0 607 461 600	M 10	8–40
0 607 461 602	M 12	8–45
0 607 452 603	M 6	10–38
0 607 452 604	M 8	16–56
0 607 452 605	M 8	20–68
0 607 452 606	M 4	2–16
Please order the angle head separately		
0 607 457 601	M 14	31–80
0 607 457 600	M 14	39–100
0 607 457 602	M 16	50–120

Tightening torque (Nm) soft screwdriving application 720°	No-load speed (rpm)	Direction of rotation	Air consumption under load (l/s) (cfm)	Weight (kg)	Hex tool-holder = internal hexagon Square = external square	Connecting thread	Hose inner diameter (mm)	Comments	Comes complete with
8-21	400	R/L	11.1 23.5	2.0	3/8" square	G 1/4"	10	Centralised exhaust air guidance	Locking hook Hose nipple G 1/4" Hanging hook Hanging hook (fitted) Hose nipple
8-21	400	R/L	11.1 23.5	2.0	1/4" hex	G 1/4"	10		
8-34	260	R/L	11.1 23.5	2.2	3/8" square	G 1/4"	10		
8-39	300	R	10.2 21.6	2.2	3/8" square	G 1/4"	10		
10-38	570	R/L	15 31.8	1.5	3/8" square	G 1/4"	10	Centralised exhaust air guidance	Hose nipple Chuck key
16-56	400	R/L	15 31.8	1.5	3/8" square	G 1/4"	10		
20-68	320	R/L	15 31.8	1.5	3/8" square	G 1/4"	10		
2-16	1200	R/L	15 31.8	1.0	-	G 1/4"	10		
								Please order the angle head separately	
31 -70	270	R/L	16.2 34.3	3.4	1/2" square	G 3/8"	10	Decentralised exhaust air guidance	Locking hook Hose nipple G 3/8" Hanging hook with support Silencer - Plastic - Sintered metal
39-90	200	R/L	16.2 34.3	3.4	1/2" square	G 3/8"	10		
50-110	100	R/L	20.0 42.3	3.6	1/2" square	G 3/8"	10		