



Tightening torque (Nm) soft screwdriving application 720°	No-load speed (rpm)	Direction of rotation	Air consumption under load (l/s) (cfm)	Weight (kg)	Toolholder QRC = quick-release chuck	Connecting thread	Hose inner diameter (mm)	Comments	Comes complete with
5.5-13	700	R/L	10.2 21.6	1.4	1/4" QRC	G 1/4"	10	Pushbutton start	Locking hook Hose nipple G 1/4" Silencer Auxiliary handle dia. 46 mm
8.5-21	400	R/L	10.2 21.6	1.4	1/4" QRC	G 1/4"	10	Pushbutton start	
8.5-21	400	R/L	10.2 21.6	1.4	7/16" QRC	G 1/4"	10	Pushbutton start	
8.5-16	800	R	9.4 19.9	1.4	1/4" QRC	G 1/4"	10	Push and push-button start	Locking hook Hose nipple G 1/4" Silencer Auxiliary handle dia. 46 mm
8.5-20	640	R	9.4 19.9	1.4	1/4" QRC	G 1/4"	10	Push and push-button start	
5.5-13	700	R/L	10.2 21.6	1.4	1/4" QRC	G 1/4"	10	Push and push-button start	
8.5-21	400	R/L	10.2 21.6	1.4	1/4" QRC	G 1/4"	10	Push and push-button start	
8.5-21	400	R/L	10.2 21.6	1.4	7/16" QRC	G 1/4"	10	Push and push-button start	
8.5-27	450	R	9.4 19.9	1.4	7/16" QRC	G 1/4"	10	Push and push-button start	