

# Lubrication-free operated centre grip screwdrivers, 180 watts

## 180-watt centre grip screwdrivers

- ▶ External torque setting without tool change
- ▶ Shut-off clutch for very fine torque setting and minimal torque dispersion
- ▶ Large torque range of 1.2 to 10 Nm
- ▶ Shut-off and lockover wrench in one due to "S-Plus" clutch
- ▶ Right-hand/left-hand rotation. Greater torque in left-hand rotation, in order to loosen screws more easily
- ▶ CLEAN technology
- ▶ Minimal air consumption
- ▶ Quick-release chuck with double bit holder
- ▶ Clutch housing for screw supply (Fig. on Page 56)

For screws from M 5 to M 6

Centre grip screwdrivers with lockover clutch



Centre grip screwdrivers with shut-off clutch



Centre grip screwdrivers with shut-off clutch



Part number	Screw dia. Quality category 8.8	Tightening torque (Nm) hard screwdriving application 30°
0 607 453 434*	M 6	1.2–10
0 607 453 438*	M 6	1.2–7
0 607 453 435	M 6	1.2–5.5
0 607 453 436	M 5	1.2–4.5
0 607 453 437	M 5	1.2–3
0 607 453 439*	M 6	1.2–10
0 607 453 441*	M 6	1.2–7
0 607 453 440	M 6	1.2–5.5
0 607 453 443	M 5	1.2–3
0 607 453 442**	M 6	0.5–2
0 607 453 429*	M 6	1.2–10
0 607 453 433*	M 6	1.2–7
0 607 453 430	M 6	1.2–5.5
0 607 453 431	M 5	1.2–4.5
0 607 453 432	M 5	1.2–3

Tightening torque (Nm) soft screwdriving application 720°	No-load speed (rpm)	Direction of rotation	Air consumption under load (l/s) (cfm)	Weight (kg)	Toolholder QRC = quick-release chuck	Connecting thread	Hose inner diameter (mm)	Comments	Comes complete with
1.2-10	380	R/L	5.5 11.7	0.9 kg	1/4" QRC	G 1/4"	6	Pushbutton start	Hose nipple G 1/4"
1.2-7	600	R/L	5.5 11.7	0.9 kg	1/4" QRC	G 1/4"	6	Pushbutton start	Silencer Chuck key
1.2-5	950	R/L	5.5 11.7	0.9 kg	1/4" QRC	G 1/4"	6	Pushbutton start	Clutch spring (yellow) or *clutch spring (blue)
1.2-3	1500	R/L	5.5 11.7	0.9 kg	1/4" QRC	G 1/4"	6	Pushbutton start	Hanging hook
1.2-2.5	2200	R/L	5.5 11.7	0.9 kg	1/4" QRC	G 1/4"	6	Pushbutton start	
1.2-10	380	R/L	5.5 11.6	0.9 kg	1/4" QRC	G 1/4"	6	Pushbutton start	Hose nipple G 1/4"
1.2-7	600	R/L	5.5 11.6	0.9 kg	1/4" QRC	G 1/4"	6	Pushbutton start	Silencer Chuck key
1.2-5	950	R/L	5.5 11.6	0.9 kg	1/4" QRC	G 1/4"	6	Pushbutton start	Clutch spring (yellow) or *clutch spring (blue) or **clutch spring (white)
1.2-3	1500	R/L	5.5 11.6	0.9 kg	1/4" QRC	G 1/4"	6	Pushbutton start	Hanging hook
0.5-2	600	R/L	5.5 11.6	0.9 kg	1/4" QRC	G 1/4"	6	Pushbutton start	
1.2-10	380	R/L	5.5 11.6	0.9 kg	1/4" QRC	G 1/4"	6	Push and push-button start	Hose nipple G 1/4"
1.2-7	600	R/L	5.5 11.6	0.9 kg	1/4" QRC	G 1/4"	6	Push and push-button start	Silencer Chuck key
1.2-5	950	R/L	5.5 11.6	0.9 kg	1/4" QRC	G 1/4"	6	Push and push-button start	Clutch spring (yellow) or *clutch spring (blue)
1.2-3	1500	R/L	5.5 11.6	0.9 kg	1/4" QRC	G 1/4"	6	Push and push-button start	Hanging hook
1.2-2.5	2200	R/L	5.5 11.6	0.9 kg	1/4" QRC	G 1/4"	6	Push and push-button start	