

Lubrication-free operated straight screwdrivers, 20 watts with integrated screw suction



For screws
from M 3 to M 6

Straight screwdrivers with
shut-off clutch



CLEAN



Straight screwdrivers with
S-Plus clutch



CLEAN



Part number	Screw dia. Quality category 8.8	Tightening torque (Nm) hard screwdriving application 30°
0 607 459 203	M 3	0.06–1
0 607 459 205	M 3	0.06–0.8
0 607 459 204	M 3	0.06–1

20-watt straight screwdrivers

- ▶ CLEAN technology
- ▶ Constant torque
- ▶ Noise-reduced
- ▶ Integrated screw suction with bit system
- ▶ Exhaust air hose optional
- ▶ Small, non-slip and breakproof plastic housing
- ▶ Minimal air consumption
- ▶ Low weight

Tightening torque (Nm) soft screwdriving application 720°	No-load speed (rpm)	Direction of rotation	Air consumption under load (l/s) (cfm)	Weight (kg)	Hex toolholder = internal hexagon QRC = quick-release chuck	Connecting thread	Hose inner diameter (mm)	Comments	Comes complete with
0.06–0.9	800	R/L	2.2	0.2	3 mm hex	M 5	4	Push start	Spring for guide sleeve Hanging hook Sintered metal silencer Clutch springs 0.06-0.3 Nm (green) 0.2-0.6 Nm (brown) 0.5-1 Nm (orange)
			4.7						
0.06–0.6	1200	R/L	2.2	0.2	3 mm hex	M 5	4	Push start	
			4.7						
0.06–0.9	800	R/L	2.2	0.2	3 mm hex	M 5	4	Push and lever start	Spring for guide sleeve Hanging hook Sintered metal silencer Clutch springs 0.2-0.6 Nm (brown) 0.06-0.3 Nm (green) 0.5-1 Nm (orange)
			4.7						

Lubrication-free operated straight screwdrivers, 120 watts

120-watt straight screwdrivers

- ▶ CLEAN technology
- ▶ External torque setting without tool change
- ▶ Shut-off clutch for very fine torque setting and minimal torque dispersion
- ▶ Large torque range of 0.8 to 7 Nm
- ▶ Shut-off and lockover wrench in one due to "S-Plus" clutch
- ▶ Right-hand/left-hand rotation. Greater torque in left-hand rotation, in order to loosen screws more easily
- ▶ Minimal air consumption
- ▶ Quick-release chuck with double bit holder
- ▶ Clutch housing for screw supply (Fig. on Page 56)

For screws from M 3 to M 6

Straight screwdrivers with lockover clutch



CLEAN

Straight screwdrivers with shut-off clutch



CLEAN

Straight screwdrivers with S-Plus clutch for bypassing shut-off



CLEAN

Part number	Screw dia. Quality category 8.8	Tightening torque (Nm) hard screwdriving application 30°
0 607 454 006	M 4	0.8–2
0 607 454 007	M 5	0.8–3.4
0 607 454 238	M 4	0.8–3
0 607 454 239	M 5	0.8–3.4
0 607 454 228	M 4	0.8–2.5
0 607 454 229	M 4	0.8–3
0 607 454 230	M 5	0.8–3.4
0 607 454 231	M 5	0.8–5
0 607 454 232	M 4	0.8–7
0 607 454 234	M 4	0.8–3
0 607 454 235	M 5	0.8–3.4
0 607 454 236	M 5	0.8–5
0 607 454 237	M 6	0.8–7

Tightening torque (Nm) soft screwdriving application 720°	No-load speed (rpm)	Direction of rotation	Air consumption under load (l/s) (cfm)	Weight (kg)	Hex toolholder = internal hexagon QRC = quick-release chuck	Connecting thread	Hose inner diameter (mm)	Comments	Comes complete with
0.8-2	1700	R/L	3.4	0.8	1/4" QRC	G 1/4"	6	Lever start	Hanging hook Hose nozzle Chuck key Clutch spring (yellow) Accessories Clutch spring 0.5-2 Nm (white)
			7.3						
0.8-3	1050	R/L	3.4	0.8	1/4" QRC	G 1/4"	6	Lever start	
			7.3						
0.8-2	1700	R/L	3.4	0.8	1/4" QRC	G 1/4"	6	Push start	
			7.3						
0.8-3	1050	R/L	3.4	0.8	1/4" QRC	G 1/4"	6	Push start	
			7.3						
0.8-1.5	2300	R/L	3.4	0.8	1/4" QRC	G 1/4"	6	Push start	
			7.3						
0.8-2	1700	R/L	3.4	0.8	1/4" QRC	G 1/4"	6	Push start	Hanging hook Hose nozzle Chuck key Clutch spring (yellow) Accessories Clutch spring 0.5-2 Nm (white)
			7.3						
0.8-3	1050	R/L	3.4	0.8	1/4" QRC	G 1/4"	6	Push start	
			7.3						
0.8-4.5	640	R/L	3.4	0.8	1/4" QRC	G 1/4"	6	Push start	
			7.3						
0.8-7	400	R/L	3.4	0.8	1/4" QRC	G 1/4"	6	Push start	
			7.3						
0.8-2	1700	R/L	3.4	0.8	1/4" QRC	G 1/4"	6	Push and lever start	
			7.3						
0.8-3	1050	R/L	3.4	0.8	1/4" QRC	G 1/4"	6	Push and lever start	
			7.3						
0.8-4.5	640	R/L	3.4	0.8	1/4" QRC	G 1/4"	6	Push and lever start	
			7.3						
0.8-7	400	R/L	3.4	0.8	1/4" QRC	G 1/4"	6	Push and lever start	
			7.3						

Lubrication-free operated straight screwdrivers, 180 watts



180-watt straight screwdrivers

- ▶ External torque setting without tool change
- ▶ Shut-off clutch for very fine torque setting and minimal torque dispersion
- ▶ Large torque range of 1.2 to 10 Nm
- ▶ Shut-off and lockover wrench in one due to "S-Plus" clutch
- ▶ Right-hand/left-hand rotation. Greater torque in left-hand rotation, in order to loosen screws more easily
- ▶ CLEAN technology
- ▶ Minimal air consumption
- ▶ Quick-release chuck with double bit holder
- ▶ Clutch housing for screw supply (Fig. on Page 56)

For screws from M 5 to M 6

Straight screwdrivers with lockover clutch



CLEAN

Straight screwdrivers with shut-off clutch



CLEAN

Straight screwdrivers with S-Plus clutch for bypassing shut-off



CLEAN

Part number	Screw dia. Quality category 8.8	Tightening torque (Nm) hard screwdriving application 30°
0 607 453 009	M 6	1.2-5.5
0 607 453 010*	M 6	1.2-7
0 607 453 233	M 5	1.2-3
0 607 453 234	M 5	1.2-4.5
0 607 453 229	M 5	1.2-4.5
0 607 453 230	M 6	1.2-5.5
0 607 453 231*	M 6	1.2-7
0 607 453 232*	M 6	1.2-10
0 607 453 235	M 5	1.2-3
0 607 453 236	M 5	1.2-4.5
0 607 453 237	M 6	1.2-5.5
0 607 453 238*	M 6	1.2-7
0 607 453 239*	M 6	1.2-10
0 607 453 240	M 6	1.2-5.5
0 607 453 241*	M 6	1.2-7
0 607 453 242*	M 6	1.2-10

Tightening torque (Nm) soft screwdriving application 720°	No-load speed (rpm)	Direction of rotation	Air consumption under load (l/s) (cfm)	Weight (kg)	Toolholder QRC = quick-release chuck	Connecting thread	Hose inner diameter (mm)	Comments	Comes complete with
1.2-5	950	R/L	5.5 11.6	0.9	1/4" QRC	G 1/4"	6	Lever start	Hanging hook Chuck key Hose nipple Clutch spring (yellow) or *clutch spring (blue)
1.2-7	600	R/L	5.5 11.6	0.9	1/4" QRC	G 1/4"	6	Lever start	
1.2-2.5	2200	R/L	5.5 11.6	0.9	1/4" QRC	G 1/4"	6	Push start	
1.2-3	1500	R/L	5.5 11.6	0.9	1/4" QRC	G 1/4"	6	Push start	
1.2-3	1500	R/L	5.5 11.6	0.8	1/4" QRC	G 1/4"	6	Lever start	
1.2-5.5	950	R/L	5.5 11.6	0.8	1/4" QRC	G 1/4"	6	Lever start	
1.2-7	600	R/L	5.5 11.6	0.9	1/4" QRC	G 1/4"	6	Lever start	Models ...232 and ...239 incl. auxiliary handle
1.2-10	380	R/L	5.5 11.6	0.9	1/4" QRC	G 1/4"	6	Lever start	
1.2-2.5	2200	R/L	5.5 11.6	0.8	1/4" QRC	G 1/4"	6	Push start	
1.2-3	1500	R/L	5.5 11.6	0.8	1/4" QRC	G 1/4"	6	Push start	
1.2-5	950	R/L	5.5 11.6	0.8	1/4" QRC	G 1/4"	6	Push start	
1.2-7	600	R/L	5.5 11.6	0.9	1/4" QRC	G 1/4"	6	Push start	
1.2-10	380	R/L	5.5 11.6	0.9	1/4" QRC	G 1/4"	6	Push start	
1.2-5	950	R/L	5.5 11.6	0.8	1/4" QRC	G 1/4"	6	Push start	
1.2-7	600	R/L	5.5 11.6	0.9	1/4" QRC	G 1/4"	6	Push start	
1.2-10	380	R/L	5.5 11.6	0.9	1/4" QRC	G 1/4"	6	Push start	
									Hanging hook Chuck key Hose nipple Clutch spring (yellow) or *clutch spring (blue)
1.2-5	950	R/L	5.5 11.6	0.8	1/4" QRC	G 1/4"	6	Push start	
1.2-7	600	R/L	5.5 11.6	0.9	1/4" QRC	G 1/4"	6	Push start	
1.2-10	380	R/L	5.5 11.6	0.9	1/4" QRC	G 1/4"	6	Push start	
									Model ...242 incl. auxiliary handle