

Straight screwdrivers

400 watts



400-watt rotary screwdrivers

- ▶ Most powerful rotary screwdriver
- ▶ External torque setting
- ▶ Wear-free shut-off clutch
- ▶ Variable due to modular system
- ▶ Ergonomic centre grip for optimum handling
- ▶ Robust, cold-insulating polyamide housing
- ▶ Exhaust air hose optional
- ▶ Low-vibration

For screws
from M 6 to M 8

**Straight screwdrivers with
lockover clutch**



**Straight screwdrivers with
shut-off clutch**



**Straight screwdrivers with
S-Plus clutch for
bypassing shut-off**



| Part number | Screw dia. Quality category 8.8 | Tightening torque (Nm) hard screwdriving application 30° |
|---------------|---------------------------------------|---|
| 0 607 461 001 | M 8 | 5.5–15 |
| 0 607 461 201 | M 6 | 5.5–10 |
| 0 607 461 202 | M 8 | 5.5–15 |
| <hr/> | | |
| 0 607 461 205 | M 6 | 5.5–10 |
| 0 607 461 203 | M 8 | 5.5–13 |
| 0 607 461 206 | M 6 | 5.5–15 |
| 0 607 461 204 | M 6 | 8–19 |
| 0 607 461 207 | M 6 | 8–19 |
| <hr/> | | |
| 0 607 461 208 | M 6 | 5.5–10 |
| 0 607 461 209 | M 8 | 5.5–15 |
| | | |
| | | |
| | | |
| | | |
| | | |

| Tightening torque (Nm) soft screwdriving application 720° | No-load speed (rpm) | Direction of rotation | Air consumption under load (l/s) (cfm) | Weight (kg) | Toolholder QRC = quick-release chuck | Connecting thread | Hose inner diameter (mm) | Comments | Comes complete with |
|---|---------------------|-----------------------|--|-------------|--------------------------------------|-------------------|--------------------------|----------------------|--|
| 5.5-14 | 700 | R/L | 11.0 23.3 | 1.3 | 1/4" QRC | G 1/4" | 10 | Lever start | Locking hook Hose nipple G 1/4" Hanging hook Auxiliary handle dia. 46 mm |
| 5.5-10 | 1050 | R/L | 11.0 23.3 | 1.3 | 1/4" QRC | G 1/4" | 10 | Push start | |
| 5.5-14 | 700 | R/L | 11.0 23.3 | 1.3 | 1/4" QRC | G 1/4" | 10 | Push start | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| 5.5-10 | 1050 | R/L | 11.0 23.3 | 1.3 | 1/4" QRC | G 1/4" | 10 | Push start | Locking hook Hose nipple G 1/4" Hanging hook Auxiliary handle dia. 46 mm |
| 5.5-13 | 1200 | R | 10.2 21.6 | 1.3 | 1/4" QRC | G 1/4" | 10 | Push start | |
| 5.5-14 | 700 | R/L | 11.0 23.3 | 1.3 | 1/4" QRC | G 1/4" | 10 | Push start | |
| 8-17 | 800 | R | 10.2 21.6 | 1.3 | 1/4" QRC | G 1/4" | 10 | Push start | |
| 8-17 | 800 | R | 10.2 21.6 | 1.3 | 1/4" QRC | G 1/4" | 10 | Lever start | |
| | | | | | | | | | |
| 5.5-10 | 1050 | R/L | 11.0 23.3 | 1.3 | 1/4" QRC | G 1/4" | 10 | Push and lever start | Locking hook Hose nipple G 1/4" Hanging hook Auxiliary handle dia. 46 mm |
| 5.5-14 | 700 | R/L | 11.0 23.3 | 1.3 | 1/4" QRC | G 1/4" | 10 | Push and lever start | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |