

Straight-, Vertical- and Angle Grinders



- ▶ Cold insulating, sturdy polyamide housing
- ▶ Slimline handle for great grip comfort
- ▶ Powerful sleeve valve motor
- ▶ Speed control for constant speed even under high load
- ▶ Waste air expelled via handle

	Part Number	Permissible sanding/ grinding accessory-l (mm)	No load speed (rpm)
Straight Grinder 	0 607 260 100	40	21 000
	0 607 260 101	40	21 000
Straight Grinder Set 	0 607 260 110	40	21 000
Straight Grinder 	0 607 252 103	40	21 000
Vertical Grinder 	0 607 360 100	75	19 000
Angle Grinder 	0 607 352 109	125	12 000
	0 607 352 113	125	12 000
	0 607 352 112	125	7 000
	0 607 352 114	125	7 000

Output (W)	Air consumption under load (l/s)	(cfm)	Weight (kg)	Toolholding fixture/spindle thread	Connecting thread	Internal hose width (mm)	Remarks	Comes complete with
320	8.5	18	0.6	6 mm collet	1/4"-NPT	10		Collet ø 6 mm or Collet ø 1/4" Collet nut Fork spanner SW10 Fork spanner SW14 Hose nipple
320	8.5	18	0.6	1/4" collet	1/4"-NPT	10		
320	8.5	18	0.6		1/4"-NPT	10		Collet ø 6 mm Collet nut Fork spanner SW17 Hose nipple
550	12.5	26.5	1.1	6 mm Collet	1/4"-NPT	10	Lock switching, speed control	Collet ø 6 mm Collet nut Fork spanner SW17 Hose nipple
320	8.5	18	0.7	3/8" 24 UNF	1/4"-NPT	10		Protective guard Flange nut Open-ended spanner Pin spanner Hose nipple Disc
550	14	29.7	1.3	M 14	1/4"-NPT	10	Lock switch with speed control	Protective guard Flange
550	14	29.7	1.3	M 14	1/4"-NPT	10	Dead man switch with speed con.	Collet nut Pin spanner
550	14	29.7	1.3	M 14	1/4"-NPT	10	Locking switch	Fork spanner SW17
550	14	29.7	1.3	M 14	1/4"-NPT	10	Dead man switch	Hose nipple Silencer Auxiliary handle

Your dealer will inform you of the complete quality accessory range available.