

SEC-ANGLE EXACT

Cordless nutrunners

Cordless nutrunners

SEC-ANGLE EXACT

- ▶ Highest repeatability:
Improved accuracy! $Cmk \geq 2,0$
Also the reaction forces could be improved.
- ▶ Lowest weight in class:
The new SEC-ANGLE EXACT models up to 25 Nm use only 9.6 volt batteries, reducing weight by 400 grams!
- ▶ Broad speed range of the complete series
- ▶ Broad torque range
- ▶ Adjustable angle heads for best ergonomics.
- ▶ Illumination of the work area.
- ▶ Overload protection for the PCB, the motor and the battery pack.
- ▶ Best ergonomics:
Small size and very well balanced.
One handed operation for On/Off and Left/Right.
- ▶ Robust and durable tool with the well known components of the ANGLE EXACT range.
- ▶ Proven and highly efficient battery technology in production quality.
You can still use your existent charging technology, battery packs and protective covers.

SEC-ANGLE EXACT!	Order number	Torque on hard joint per ISO 5393 (Nm)	Torque on soft joint per ISO 5393 (Nm)
	0 602 492 611	2 – 7 (1.5 – 5.1 ft.-lbs.)	2 – 6.5 (1.5 – 4.8 ft.-lbs.)
	0 602 492 612	2 – 7 (1.5 – 5.1 ft.-lbs.)	2 – 6.5 (1.5 – 5.1 ft.-lbs.)
	0 602 492 609	2 – 10 (1.5 – 7.4 ft.-lbs.)	2 – 9 (1.5 – 6.6 ft.-lbs.)
	0 602 492 610	2 – 10 (1.5 – 7.4 ft.-lbs.)	2 – 9 (1.5 – 6.6 ft.-lbs.)
	0 602 492 607	2 – 14 (1.5 – 10 ft.-lbs.)	2 – 14 (1.5 – 10 ft.-lbs.)
	0 602 492 608	2 – 14 (1.5 – 10 ft.-lbs.)	2 – 14 (1.5 – 10 ft.-lbs.)
	0 602 492 605	10 – 25 (7.4 – 18.4 ft.-lbs.)	10 – 20 (7.4 – 14.7 ft.-lbs.)
	0 602 492 606	10 – 25 (7.4 – 18.4 ft.-lbs.)	10 – 20 (7.4 – 14.7 ft.-lbs.)
	0 602 492 603	10 – 25 (7.4 – 22.1 ft.-lbs.)	10 – 25 (7.4 – 18.4 ft.-lbs.)
	0 602 492 604	10 – 30 (7.4 – 22.1 ft.-lbs.)	10 – 25 (7.4 – 22.1 ft.-lbs.)
	0 602 492 601	10 – 40 (7.4 – 29.5 ft.-lbs.)	10 – 35 (7.4 – 25.8 ft.-lbs.)
	0 602 492 602	10 – 40 (7.4 – 29.5 ft.-lbs.)	10 – 35 (7.4 – 25.8 ft.-lbs.)
	0 602 492 613	10 – 50 (7.4 – 36.9 ft.-lbs.)	10 – 45 (7.4 – 33.1 ft.-lbs.)
	0 602 492 614	10 – 50 (7.4 – 36.9 ft.-lbs.)	10 – 45 (7.4 – 33.1 ft.-lbs.)

C-EXACT	EXACT	BT-EXACT	SEC-EXACT	ACCESSORIES
---------	-------	----------	------------------	-------------

No-load speed (min ⁻¹)	Angle head	Battery specifications (V)	Direction of rotation	Weight (kg / lbs)	Features	Included accessories
900	–	–	R/L	1.0 / 2.2	0.7 repeat protection	Torque adjustment tool Spanner Hanger light blue color ring
900	–	9.6 V / 1.7 Ah	R/L	1.4 / 3.1	0.7 repeat protection	
650	–	–	R/L	1.0 / 2.2	0.7 repeat protection	Torque adjustment tool Spanner Hanger light green color ring
650		9.6 V / 1.7 Ah	R/L	1.4 / 3.1	0.7 repeat protection	
420	–	–	R/L	1.0 / 2.2	0.7 repeat protection	Torque adjustment tool Spanner Hanger white color ring
420		9.6 V / 1.7 Ah	R/L	1.4 / 3.1	0.7 repeat protection	
245	3/8" square	–	R/L	1.57 / 3.5	0.7 repeat protection	Torque adjustment tool Spanner Hanger grey blue color ring
245	3/8" square	9.6 V / 1.7 Ah	R/L	2.0 / 4.4	0.7 repeat protection	
380	3/8" square	–	R/L	1.58 / 3.5	0.7 repeat protection	Torque adjustment tool Spanner Hanger orange color ring
380	3/8" square	14.4 V / 2.4 Ah	R/L	2.3 / 5.1	0.7 repeat protection	
280	3/8" square	–	R/L	1.58 / 3.5	0.7 repeat protection	Torque adjustment tool Spanner Hanger red color ring
280	3/8" square	14.4 V / 2.4 Ah	R/L	2.3 / 5.1	0.7 repeat protection	
210	3/8" square	–	R/L	1.58 / 3.5	0.7 repeat protection	Torque adjustment tool Spanner Hanger black color ring
210	3/8" square	14.4 V / 2.4 Ah	R/L	2.3 / 5.1	0.7 repeat protection	